



Dry-wrap coupling belts

Power at its best



SWR Dry-wrap coupling belts

SWR dry-wrap coupling belts are based on over 30 years of experience in the field of mowing technology for lawn cutting.

SWR coupling belts have a long lasting high dimensional stability and heat resistance with extremely low stretch, even under high loads.

These features are made possible by a high-quality polychloroprene rubber compound, Aramid cord cables and a wear-resistant textile wrapping.

By using SWR Lawn and Garden LG Belts, the mower deck can be disengaged without any problems under all operating conditions.

For many years SWR LG belts are successfully used in big quantities also in the USA, the by far biggest lawn mower market in the world.



Simply use our experience!

To meet the different operating conditions, we use our SWR 3L-LG, 4L-LG and 5L-LG coupling belts.

We have in our stock:

Type	Regular length range mm	Regular length range $\frac{1}{10}$ = inch		Type	Regular length range mm	Regular length range $\frac{1}{10}$ = inch
3L-LG 170	432 mm La	17 inch	to	3L-LG 800	2032 mm La	80 inch
4L-LG 170	432 mm La	17 inch	to	4L-LG 1070	2718 mm La	107 inch
5L-LG 280	711 mm La	28 inch	to	5L-LG 1250	3175 mm La	125 inch

Further length on request.





If you have any questions, please do not hesitate to contact us.



SWR Europe - van Dinther Antriebstechnik GmbH
Engelbertstr. 17-21
45892 Gelsenkirchen / Germany
Tel.: +49 (0)209 177 554 20
Email: info@swr-europe.de
Web: www.swr-europe.de

